



PRINT



GLOSSARY



**View MSDS :**    1   2   3   4   5   6   7   8   9   10   11   12   13   14   15   16  
**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:**                    **KILZ® Casual Colors® Interior Flat White**  
**MSDS Manufacturer Number:** M305  
**Manufacturer Name:**            Masterchem Industries LLC  
**Address:**                            3135 Old Highway M  
     Imperial, MO 63052-2834  
  
**General Phone Number:**        (636) 942-2510  
**General Fax Number:**            (636) 942-3663  
**Customer Service Phone  
 Number:**                            (800) 325-3552  
  
**CHEMTREC:**                        For emergencies in the US, call CHEMTREC: 800-424-9300  
**Canutec:**                            In Canada, call CANUTEC: (613) 996-6666 (call collect)  
**MSDS Creation Date:**            06/26/2006  
**MSDS Revision Date:**            09/08/2008

**NFPA**

1  
 1   0  
 NA

**HMS**

<b>Health Hazard</b>	<b>1</b>
<b>Fire Hazard</b>	<b>1</b>
<b>REACTIVITY</b>	<b>0</b>
<b>Personal Protection</b>	<b>X</b>

\* **Chronic Health  
 Effects:**

**SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Chemical Name</b>	<b>CAS#</b>	<b>Ingredient Percent</b>
Aluminum hydroxide	21645-51-2	1 - 5 by weight
Anhydrous aluminum silicate	66402-68-4	5 - 10 by weight
Ethylene glycol	107-21-1	1 - 5 by weight
Nepheline Syenite	37244-96-5	1 - 5 by weight
Non hazardous ingredient(s)	No data	30 - 60 by weight
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5 by weight
Styrene/acrylic copolymer	No data	1 - 5 by weight
Titanium dioxide	13463-67-7	10 - 30 by weight
Undisclosed/Proprietary	No data	1 - 5 by weight
Vinyl acrylic polymer	No data	10 - 30 by weight

**SECTION 3 - HAZARDS IDENTIFICATION**

**Emergency Overview:**            Irritant.  
**Potential Health Effects:**  
**Eye:**                                    May cause irritation.  
**Skin:**                                    May cause irritation.  
**Inhalation:**                        Prolonged or excessive inhalation may cause respiratory tract irritation.  
**Ingestion:**                         May be harmful if swallowed. May cause vomiting.

Chronic Health Effects:	Prolonged or repeated contact may cause skin irritation.
Signs/Symptoms:	Overexposure may cause headaches and dizziness.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	None generally recognized.

---

#### SECTION 4 - FIRST AID MEASURES

---

Eye Contact:	Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid:	Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

---

#### SECTION 5 - FIRE FIGHTING MEASURES

---

Flash Point:	No Data
Lower Flammable/Explosive Limit:	Not applicable.
Upper Flammable/Explosive Limit:	Not applicable.
Extinguishing Media:	Use alcohol foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

**NFPA Ratings:**

NFPA Flammability:	1
NFPA Health:	1
NFPA Reactivity:	0
NFPA Other:	NA

---

#### SECTION 6 - ACCIDENTAL RELEASE MEASURES

---

Personnel Precautions:	Use proper personal protective equipment as listed in section 8.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section.

---

#### SECTION 7 - HANDLING and STORAGE

---

Handling:	Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.
Hygiene Practices:	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

---

#### SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

---

<b>Engineering Controls:</b>	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
<b>Eye/Face Protection:</b>	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
<b>Skin Protection Description:</b>	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
<b>Respiratory Protection:</b>	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
<b>Other Protective:</b>	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

---

#### EXPOSURE GUIDELINES

##### Ethylene glycol :

Guideline ACGIH: TLV-STEL: C 100 mg/m3 (Aerosol only)

##### Silica, amorphous, precipitated and gel :

Guideline ACGIH: TLV-TWA: 10 mg/m3

Guideline OSHA: OSHA-TWA: 20 mg/m3

##### Titanium dioxide :

Guideline ACGIH: TLV-TWA: 10 mg/m3

Guideline OSHA: OSHA-TWA: 15 mg/m3

---

## SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

---

<b>Physical State Appearance:</b>	Liquid.
<b>Color:</b>	White
<b>Flash Point:</b>	No Data
<b>Boiling Point:</b>	No Data
<b>Melting Point:</b>	No Data
<b>Density:</b>	10 - 12 Lbs./gal.
<b>Vapor Density:</b>	Greater than 1 (Air = 1).
<b>pH:</b>	No Data
<b>Molecular Formula:</b>	Mixture
<b>Molecular Weight:</b>	Mixture
<b>Flash Point:</b>	No Data
<b>VOC Content:</b>	Material VOC: 40 gm/l (Includes Water) Coating VOC.: 99 gm/l (Excludes Water)

---

## SECTION 10 - STABILITY and REACTIVITY

---

<b>Chemical Stability:</b>	Stable under normal temperatures and pressures.
<b>Hazardous Polymerization:</b>	Not reported.
<b>Conditions to Avoid:</b>	Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.
<b>Incompatible Materials:</b>	Oxidizing agents. Strong acids and alkalis.

---

## SECTION 11 - TOXICOLOGICAL INFORMATION

---

RTECS Number:	BD0940000
<b>Ethylene glycol :</b>	
RTECS Number:	KW2975000
Eye:	Eye - Rabbit; Standard Draize Test. : 500 mg/24H; mild. Eye - Rabbit; Standard Draize Test. : 1440 mg/6H; Moderate. (RTECS)
Skin:	Skin - Rabbit; Open irritation : 555 mg; mild. (RTECS)
Inhalation:	Inhalation. - Rat LC: >200 mg/m3/4H; Details of toxic effects not reported other than lethal dose value. Inhalation. - Mouse LC: >200 mg/m3/2H; Details of toxic effects not reported other than lethal dose value. (RTECS)
Ingestion:	Ingestion - Rat LD50: 4700 mg/kg; Details of toxic effects not reported other than lethal dose value.. (RTECS)
RTECS Number:	VV7315000
<b>Titanium dioxide :</b>	
RTECS Number:	XR2275000
Skin:	Skin - Rabbit; Standard Draize Test. : 300 ug/3D; (Intermittent) mild. (RTECS)
Ingestion:	Ingestion - Rat TDLo: 60 gm/kg; Gastrointestinal - hypermotility, diarrhea Gastrointestinal - other changes. (RTECS)

---

## SECTION 12 - ECOLOGICAL INFORMATION

---

Ecotoxicity:	No ecotoxicity data was found for the product.
Environmental Fate:	No environmental information found for this product.

---

## SECTION 13 - DISPOSAL CONSIDERATIONS

---

Waste Disposal:	Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.
-----------------	---

---

## SECTION 14 - TRANSPORT INFORMATION

---

DOT UN Number:	No Data
DOT Hazard Class:	No Data

---

## SECTION 15 - REGULATORY INFORMATION

---

<b>Aluminum hydroxide :</b>	
TSCA Inventory Status:	Listed
Canada DSL:	Listed
<b>Anhydrous aluminum silicate :</b>	
TSCA Inventory Status:	Listed
Canada DSL:	Listed
<b>Ethylene glycol :</b>	
TSCA Inventory Status:	Listed
State Regulations:	Listed in the New Jersey State Right to Know List. Listed in the Pennsylvania State Hazardous Substances List.
Canada DSL:	Listed
<b>Nepheline Syenite :</b>	
TSCA Inventory Status:	Not listed
Canada DSL:	Listed
<b>Silica, amorphous, precipitated and gel :</b>	
TSCA Inventory Status:	Not listed
Canada DSL:	Listed

**Titanium dioxide :**

TSCA Inventory Status: Listed  
State Regulations: Listed in the New Jersey State Right to Know List.  
Listed in the Pennsylvania State Hazardous Substances List.  
Canada DSL: Listed  
WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

---

**SECTION 16 - ADDITIONAL INFORMATION**

---

HMIS Fire Hazard: 1  
HMIS Health Hazard: 1  
HMIS Reactivity: 0  
HMIS Personal Protection: x  
HMIS Other: x  
MSDS Creation Date: 06/26/2006  
MSDS Revision Date: 09/08/2008  
MSDS Revision Notes: Quarterly formula update  
MSDS Author: Actio Corporation  
Disclaimer: This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.  
Trademark: The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights Reserved.

Copyright© 1996-2008 [Actio Software Corporation](#). All Rights Reserved.